

RIKO EKOS d.o.o.

Mali log 2a -1318 Loški Potok

☎ 00386-1-8367-056, fax 00386-1-8367-040

E-mail: info@riko-ekos.si

Web: www.riko-ekos.si

VERTICAL BALER							
Technical data		S-6	S-10	S-20	S-50	S-5AD	S-20AD
BALER DIMENSIONS							
Depth	mm	800	1000	1300	2032	890	1200
Width	mm	990	1145	1450	1308	2000	2580
Height	mm	2500	2735	3240	3531	1970	2870
Weight	kg	430	650	1500	2100	560	1500

DIMENSIONS OF CHAMBER							
Width	mm	800	900	1250	1524	750	1100
Depth	mm	500	700	950	762	550	700
Bale ejection system		Yes	Yes	Yes	Yes	No	Yes
Bale ties	Nr.	3	3	4	6	3	4

HYDRAULICS							
Motor	kW	1,5 (3x400 V)	3 (3x400V)	5 (3x400V)	7,5 (3x400V)	1,5 (230V)	5,5 (3x400v)
Internal pump		Yes	Yes	Yes	Yes	Yes	Yes
Hydraulic valves	V	24	24	24	24	24	24
Pressure force max.	ton	6	10	20	35	5	20
Specific pressure	Kg/cm ²	1,5	1,6	1,7	3,0	1,25	2,59

BALE							
Width	mm	800	900	1250	1524	750	1200
Depth	mm	500	700	950	762	550	800
Height	mm	600	600	850	1220	800	1000
Bale weight	kg	40-80	100-150	250-300	300-500	30-60	120-300

CAPACITY							
Chamber volume	m ³	0,52	0,82	1,78	1,94	0,37	0,86
Cycle time-empty	sec	30	30	45	52	30	28
Approximate capacity	kg/h	45-170	80-200	300-600	400-800	45-170	120-450
ELECTRIC							
Control voltage	V	24	24	24	24	24	24
PLC		No	No	No	Mitchubishi	No	No
Safety switches (doors)		Yes	Yes	Yes	Yes	Yes	Yes
Electrical equipment: Telemecanique							
PAINTING							
Two component paint colour used as base and final layer. Metal parts are washed and grind before painting							
SAFETY SYSTEM							
Two hand control		Yes	Yes	Yes	Yes	Yes	Yes
Guardmaster interlocking safety switch with dual redundancy guard protecting		Yes	Yes	Yes	Yes	Yes	Yes
NOISE LEVEL							
	db	<75	<75	<80	<80	<75	<80
BINDING WIRE							
		Straps polypropilen	Straps polypropilen	Straps polypropilen	Straps polypropilen Annealed wire	Straps polypropilen	Straps polypropilen
CE							
Baler is made according CE request including necessary documentation.							

A – ONE CHAMBER BALER
AD- TWO CHAMBER BALER